



# FirePro® Flex Seal Linear Joint

## A flexible firestop solution for linear joint applications

The FirePro Flex Seal Linear Joint has been developed as a fire-stopping solution capable of accommodating high levels of movement in building services and structural joints.

Specifically engineered for linear joint seal applications where high movement tolerance and fire resistance are essential performance requirements.

- Tested in accordance with EN 1366-4: 2021
- Classified in accordance with EN 13501-2: 2023
- Certified by UL, Certification No: UL-EU-01351-EN
- Non-combustible stone wool core
- Pre coated with Flex Seal Coating
- Suitable for vertical and horizontal joint applications

# FirePro® Flex Seal Linear Joint



## APPLICATIONS

FirePro Flex Seal Linear Joint can be installed horizontally or vertically and is suitable for linear joint widths up to 200mm.

It can also be used as a 'head-of-wall' barrier to extend the fire resistance and acoustic performances of masonry walls that finish at suspended ceiling height, up to the concrete soffit above and with ROCKWOOL CB50/60 for head-of-wall applications.

Depending on the application, FirePro Flex Seal Linear Joint can be supplied on either one or both sides. (Single Sided for Horizontal Applications. Double sided for Vertical Applications).

# FirePro® Flex Seal Linear Joint

## PERFORMANCE

### Fire performance

FirePro Flex Seal Linear Joint has been tested as a linear joint seal to EN 1366-4: 2021 and has been classified for fire resistance periods of up to 2 hours (EI 120), subject to the application.

FirePro Flex Seal Linear Joint has been certified by UL Certification No: UL-EU-01351-EN

### Movement

As part of the testing EN 1366-4: 2021 FirePro Flex Seal was assessed for its movement capabilities, prior to conducting the fire test. The product was tested to accommodate movement (expansion and contraction) of +/-25%.

### Acoustics

- Tested in a double layered plasterboard internal partition.
- 300x300mm square framed and lined opening.
- Single 100mm FirePro Flex Seal set within depth of opening 48(-1;-3) RW (C;Ctr)
- Tests were conducted in a 300mm wall partition wall.

## PRODUCT INFORMATION

Property	Description
Length	1200mm
Width	200mm
Thickness	100mm
Fire resistance	Up to 2 hours (EI 120)
Coating	Flex Seal Coating single sided
Movement	+/-25%

## STANDARDS AND APPROVALS

Certificate
Tested in accordance with EN 1366-4: 2021
Third party certification through UL, Certificate No. UL-EU-01351-EN

# FirePro® Flex Seal Linear Joint

## BUILDING SAFETY AND PRODUCT USE

### LEGAL NOTICES

#### General safety requirements – Building Safety Act 2022

ROCKWOOL Limited is committed to supporting specifiers, resellers and users of ROCKWOOL products for the full life cycle of the product to comply with the obligations and responsibilities set out in the Building Safety Act 2022. With regard to the general safety requirements of the Act, ROCKWOOL Limited cannot control or foresee every situation where its products might be used. We therefore strongly advise that specifiers, resellers and users contact us where use of ROCKWOOL products is contemplated in applications different from those explicitly described in the latest, relevant ROCKWOOL product datasheets; especially in applications that can be reasonably foreseen as critical to safety.

ROCKWOOL Limited reserves the right to amend the specification of its products without notice. Changes to the ROCKWOOL manufacturing process, or to pertinent regulations, may be reflected in changes to tested and certified product performance. Whilst ROCKWOOL Limited endeavours to keep its publications up to date, readers will appreciate that between publications there may be pertinent changes in the law or other developments affecting the accuracy of the information contained in our publications.

ROCKWOOL Limited does not accept responsibility for the consequences of using (including testing or certifying) its products in applications different from those explicitly described in the relevant ROCKWOOL product datasheets. Expert advice should be sought, and ROCKWOOL Limited should be contacted, where such different use is contemplated, or where the extent of any use described by ROCKWOOL Limited is in doubt.

#### The ROCKWOOL Trademark

ROCKWOOL® - our trademark

The ROCKWOOL trademark was initially registered in Denmark as a logo mark back in 1936. In 1937, it was accompanied with a word mark registration; a registration which is now extended to more than 60 countries around the world.

The ROCKWOOL trademark is one of the most important assets of the ROCKWOOL Group, and is therefore well-protected and defended by ROCKWOOL throughout the world.

If you require permission to use the ROCKWOOL logo for your business, advertising or promotion, you must apply for a Trade Mark Usage Agreement.

To apply, write to:  
[marketcom@rockwool.com](mailto:marketcom@rockwool.com)

#### Trademarks

Registered trademarks of the ROCKWOOL Group include but are not limited to:

ROCKWOOL®, RockClose®, RainScreen Duo Slab®, HardRock®, RockFloor®, Flexi®, RockFall®, FirePro®, DuctRock®, BeamClad®, NyRock®

© ROCKWOOL 2025.  
All rights reserved.

#### Photography and illustrations

The product illustrations are the property of ROCKWOOL Limited and have been created for indicative purposes only.

Unless indicated below, the photography and illustrations used in this guide are the property of ROCKWOOL Limited. We reserve all rights to the usage of these images.

If you require permission to use ROCKWOOL images, you must apply for a Usage Agreement.

To apply, write to:  
[marketcom@rockwool.com](mailto:marketcom@rockwool.com)

# FirePro® Flex Seal Linear Joint

Company:	ROCKWOOL Limited
Version:	Version 1.00 September 2025 <i>(to check this is the latest version, please refer to <a href="http://rockwool.com/uk">rockwool.com/uk</a>)</i>
Revised on:	25.09.25
Product Name:	FirePro® Flex Seal Linear Joint
Replaces Version:	
Changes Made:	
Additional Information:	

*Please ensure you are using the latest version of this document by verifying it on our official website. Do not rely on printed or previously downloaded copies, as these may be out of date.*

*Please contact the ROCKWOOL Technical Support Team if you would like to access archived versions of this document.*

# FirePro® Flex Seal Linear Joint

## ROCKWOOL stone wool - safe to install and live alongside

There are no hazardous classifications associated with stone wool insulation manufactured by ROCKWOOL-UK according to EU REACH and UK REACH regulations on health and the environment. ROCKWOOL safe use instruction sheets and material safety data sheets (where applicable) can be downloaded [here](#).




### Sustainability

ROCKWOOL products are used to enrich modern living, creating safer, healthier and more climate-resilient communities.

We transform abundant, natural volcanic rock into stone wool insulation products that are used to reduce energy demand, lower fuel bills and help address society's climate change challenges.

ROCKWOOL stone wool insulation is recyclable and can be transformed into new ROCKWOOL products. Please contact us for details of how we can work together to recycle waste ROCKWOOL stone wool material that may be generated during on-site installation.

Our annual sustainability reports, which set out progress against our sustainability goals, and further details of the positive impacts of using our products can be found on our website.



### Environment

ROCKWOOL takes a fact-based, auditable approach to documenting our progress in maximising our products' positive impact and minimising the effect our operations have on the environment, backed by third-party references and methodologies. Further details can be found online in our annual sustainability report.

Our high-tech production process uses filters, pre-heaters, after-burners and other cleaning and collection systems that help to reduce the effects of our manufacturing operations on the environment. ROCKWOOL stone wool insulation does not contain (and has never contained) gases that have ozone depletion potential (ODP) or global warming potential (GWP).

